

# Thickness Gages

## SERIES 547, 7

Thickness Gages offer a quick and efficient means of inspection with their convenient grip handle, thumb trigger and spring-loaded spindle. The various models cover a wide range of applications.

### FEATURES

- Wide range of applications with various types of measuring faces (on the spindle and anvil).

- The digital models incorporate Mitutoyo's popular ID-C and ID-S Series Digimatic Indicators to provide error-free LCD readings as well as data output for SPC analysis.
- **547-401 (547-400S)** is ideally suited for measuring thicknesses of paper, film, wire, sheet metal and similar materials.

### Standard Type / Digital



### Deep Throat Type / Digital



### Standard Type / Dial




### Deep Throat Type / Dial



### High Accuracy Type / Digital



### DIMENSIONS



SPC

ABSOLUTE<sup>®</sup>  
Absolute System Patented by MITUTOYO

(Refer to page VIII for details.)

### Technical Data of Digital Models

Accuracy: Refer to the list of specifications (excluding quantizing error)

Resolution:

0.01mm type	0.01mm
0.001mm type	0.001mm/0.001mm
.0005"/0.01mm type	.0005"/0.01mm
.00005"/0.001mm type	.0005"/.0001"/.00005"/0.01mm/0.001mm

Display: LCD

Scale type: ABSOLUTE electrostatic linear encoder

Max. response speed: Unlimited

Measuring force: Refer to the list of specifications

Stem dia.: 8mm (ISO/JIS type) or 3/8" (ANSI/AGD type)

Battery: SR44 (1 pc.), **938882**

Battery life: Approx. 7,000 hours under normal use

Dust/Water protection level: IP42 or IP53 (dust-proof type)

### Functions of Digital Models

Origin-set/Preset, Zeroset, GO/±NG judgment, Counting direction switching, Power ON/OFF, Simplified calculation, Function lock, Data hold, Data output, inch/mm conversion (inch/mm models)

Alarm: Low voltage, Counting value composition error, Overflow error, Tolerance limit setting error

### Optional Accessories

**905338:** SPC cable (1m) for digital models

**905409:** SPC cable (2m) for digital models

**02AZD790F:** SPC cable for U-WAVE (160mm)

**902011:** Spindle lifting lever (ISO/JIS type)\*

**902794:** Spindle lifting lever (ANSI/AGD type)\*

**137693:** Spindle lifting hook\*\*

**540774:** Spindle lifting cable

**125317:** Spare rubber boot (for dust-proof type)

**02ACA571:** Auxiliary spindle spring for 25mm/1" models\*\*\*

**02ACA773:** Auxiliary spindle spring for 50mm/2" models\*\*\*

—: Backs (See page F-40.)

—: Contact points (See page F-36.)

\*Can be used on 12mm/.5" models only.

\*\*Can be used on 25mm/1" or 50mm/2" models.

\*\*\*Required when orienting the indicator upside down.

### DIMENSIONS

